Specifications: iPF6300S

Model Class Ink Type Pigment ink; LUCIA FX;8-color pigment ink: BK, MBK, C, M, Y, PC, PM, GY 2400 x 1200dpi User installation PRINTING SPEEDS (AT ROLL) Plain Paper Coated Paper Coated Paper Photo Glossy Paper Installation conditions PRINTER STAND Type Installation conditions DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg) Main unit with Auto Roll Feed Unit (standard) Main unit and Printer Stand DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg) Main unit (standard) Main unit (pallet included) Printer Stand Printer Stand POWER Input power Power consumption Power Save Mode 100 V - 120 V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic power MEMORY Meximum Print Resolution (kg, MBK, C, M, Y, PC, PM, GY 2400 x 1200dpi User installation 035 (Fast Economy) 1:56 (Standard) 1:02 (Fast Economy) 1:56 (Standard) 2:08 (Fast Eco
PRINTING SPEEDS (A1 ROLL) Plain Paper Coated Paper 1:56 (Standard) 1:02 (Fast Economy) 1:56 (Standard) 2:08 (Fast Economy) 1:56 (Standard) 2:08 (Fast Economy) 3:08 (Standard) PRINTER STAND Type Installation conditions DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg) Main unit with Auto Roll Feed Unit (standard) Main unit and Printer Stand 1,177 (W) x 670 (D) x 344 (H) mm; Weight: approx. 51kg (excluding consumables and Printer Stand) 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66kg (excluding consumables) DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg) Main unit (pallet included) Printer Stand 1,175 (x) x 864 x 237 mm, Weight: approx. 79 kg 1,115 x 864 x 237 mm, Weight: approx. 22 kg POWER Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure Acoustic power ACOUSTIC NOISE Acoustic power
Plain Paper Coated Paper Photo Glossy Paper Photo Glossy Paper Photo Glossy Paper Type Installation conditions DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg) Main unit and Printer Stand Type (excluding consumables and Printer Stand) 1,177 (W) x 670 (D) x 344 (H) mm; Weight: approx. 51kg (excluding consumables and Printer Stand) 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66kg (excluding consumables) DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg) Main unit (pallet included) Printer Stand 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66kg (excluding consumables) POWER Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure Acoustic power Ostionary 1.56 (Standard) 2.08 (Fast Economy) 1.56 (Standard) 2.08 (Standard) 2.08 (Standard) 2.08 (Standard) 2.08 (Standard) 2.08 (Standard) 2.08 (Fast Economy) 1.56 (Standard) 2.08 (Sta
Installation conditions DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg) Main unit with Auto Roll Feed Unit (standard) Main unit and Printer Stand DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg) Main unit (pallet included) Printer Stand 1,177 (W) x 870 (D) x 9344 (H) mm; Weight: approx. 51 kg (excluding consumables and Printer Stand) 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66 kg (excluding consumables) DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg) Main unit (pallet included) Printer Stand 1,117 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,320 (W) x 914 (D) x 645 (H) mm; Weight: approx. 79 kg 1,115 x 864 x 237 mm, Weight: approx. 22 kg POWER Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operation: 100 W or less 7 W or less 7 W or less 7 W or less 7 W or less 1 W or less 1 W or less 2 Temperature: 15 - 30°C, Humidity: 10 - 80 % ACOUSTIC NOISE Acoustic power Acoustic power Acoustic power
Installation conditions DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg) Main unit with Auto Roll Feed Unit (standard) Main unit and Printer Stand DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg) Main unit (pallet included) Printer Stand Printer Stand 1,177 (W) x 870 (D) x 944 (H) mm; Weight: approx. 51 kg (excluding consumables and Printer Stand) 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 944 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables and Printer Stand) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables and Printer Stand) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 66 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 20 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 20 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 20 kg (excluding consumables) 1,177 (W) x 870 (D) x 94 (H) mm; Weight: approx. 20 kg (excluding consumables) 1,177 (W) x 670 (D) x 94 (H) mm; Weight: approx. 20 kg
DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg) Main unit with Auto Roll Printer Stand Main unit (palte included) Printer Stand Prower Power consumption PowerSave Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure ACOUSTIC NOISE Acoustic power Power Land (Name) ACOUSTIC NOISE Acoustic power
Main unit with Auto Roll Feed Unit (standard) Main unit and Printer Stand) DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg) Main unit (pallet included) Printer Stand 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66kg (excluding consumables) Main unit (pallet included) Printer Stand 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66kg (excluding consumables) Main unit (pallet included) Printer Stand 1,320 (W) x 914 (D) x 645 (H) mm; Weight: approx. 79 kg 1,115 x 864 x 237 mm, Weight: approx. 22 kg POWER Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure Acoustic power Acoustic power Acoustic power
(Packaged) W x D x H (mm), (kg) Main unit (pallet included) Printer Stand POWER Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure Acoustic power Aco
Printer Stand POWER Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure Acoustic power 1,115 x 864 x 237 mm, Weight: approx. 22 kg AC 100 - 240 V 50 - 60 Hz) Operation: 100 W or less 6 W or less 7 W or less 1 W or less 1 W or less 7 Temperature: 15 - 30°C, Humidity: 10 - 80 % Operation: 47dB (A), Standby: 35 dB (A) or less Operation: approx 6.4Bels,
Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure Acoustic power ACOUSTIC NOISE ACOUSTIC NOISE Operation: 47dB (A), Standby: 35 dB (A) or less Operation: approx 6.4Bels,
Power consumption Power Save Mode 100 V - 120 V 220 V - 240 V Power off (standby) Operational Environment ACOUSTIC NOISE Acoustic pressure Acoustic power Acoustic power Acoustic power Acoustic power Acoustic power Operation: 47dB (A), Standby: 35 dB (A) or less Operation: approx 6.4Bels,
ACOUSTIC NOISE Acoustic pressure Operation: 47dB (A), Standby: 35 dB (A) or less Operation: approx 6.4Bels,
Acoustic power Standby: 35 dB (A) or less Operation: approx 6.4Bels,
MEMORY
Standard memory 384 MB
PRINTER LANGUAGES
Printer language GARO (Graphic Arts language with Raster Operations)
OPERATION PANEL
Display Displayable Language on LCD US-English, French, German, Italian, Spanish, Russian,
INTERFACE
Hi-Speed USB Built-in Ethermet Built-in Standard 10base-T, 100base-TX, 1000base-T Protocol IPX/SPX, SNMP HTTP, TCP/IP (IPv4/IPv6), AppleTalk
PRINT HEAD
Model Type Type Head configuration Nozzle pitch Droplet size Model PF-05 Bubble-jet on demand 6 colours integrated type (2 print head) 1, 200 dpi x 2 4 pl
INKTANK
Model Colours Capacity PFI-105: BK, MBK, C, M, Y, PC, PM, GY BK, MBK, C, M, Y, PC, PM, GY Starter use: 90 ml, Sales use: 130 ml

/	
CUTTER	
Туре	Automatic horizontal cutting Rotary cutter, independent unit
MEDIA HANDLING	
Roll paper Manual feed (1 sheet) Media types	One Roll (top-loading [front operation possible], front output) Front loading and front output, top loading and front output Plain and coated paper, technical paper, film, photographic paper, proofing paper, backlit, self adhesive, banner and sign, fine art printing material
MEDIA SIZE	
Media Core size	Internal diameter of roll core: 2" / 3"
MEDIA THICKNESS	
Roll paper Manual feed from the top Manual feed from the front	0.07 - 0.8 mm 0.07 - 0.8 mm 0.5 - 1.5 mm
MEDIA WIDTH	
Roll paper Manual feed from the top Manual feed from the front	203.2 mm - 610 mm 203.2 mm - 610 mm 250 - 610 mm (24"); POP board use only: A2, A1
MINIMUM PRINTABLE LENGTH	
Roll paper Manual feed from the top Manual feed from the front	203.2 mm 279.4 mm 350 mm
MAXIMUM PRINTABLE LENGTH	
Roll paper Manual feed from the top Manual feed from the front	18 m (Varies according to the OS and application) 1.6 m 914 mm
BORDERLESS PRINTING (ROLL MEDIA ONLY)	
Media width	10" (254 mm), B4 (257 mm), A3+ (329 mm), 14" (356 mm), 16" (407 mm), A2 (420 mm), A2+/17" (432 mm), B2 (515 mm), A1 (594 mm), 24" (610 mm)
MEDIA FEED CAPACITY	
Manual feed	1 sheet (from top, from front)
REGULATIONS	Electrical safety regulations
Europe Germany Russia Other countries	CE mark TUV Gost-R (locally obtained) CB certification
ENVIRONMENT CERTIFICATIONS	
	ENERGY STAR WW, RoHS directive, IT ECO Declaration Europe, WEEE, ErP Lot 6 (Europe)
OPTION	
Printer stand Roll Holder Set (3-inch core spindle)	ST-25 RH2-25 (2-inch core roll holder with 3-inch paper tube attachment and borderless print spacer)
CONSUMABLES	
Ink Tank Print Head Maintenance Cartridge	PFI-105: BK, MBK, C, M, Y, PC, PM, GY PF-05 MC-16
This leaflet and the specifications of the productions are subject to change with	oduction. All data is based on Canon's standard testing methods, uct have been developed prior to the date of product launch. hout notice." and e? All company and/or product names are heir respective manufacturers in their markets and/or countries.
Canon recommends you use Canon Media for to see which variety of paper/media is recom	or the best results. Please check media (paper) compatibility list imended.













Canon Inc. canon.com

Canon Europe canon-europe.com

English Edition © Canon Europa N.V., 2011

