HP Designjet 4000 Printer series

Technical specifications

Print speed	25 sec D/A1-size α, 93 sgm/hour α, 1000 sqft/hour α, up to 100 D/A1-size prints per hour α
Resolution, maximum	Up to 2400 x 1200 optimized dpi (4
Line accuracy	±0.1 percent (s
Print margins	
Тор	0.45in/11.5mm (Normal); 2.1in/55mm (Extended)
Bottom	0.2in/Smm (Roll); 0.98in/25mm (Sheet Normal); 2.1in/55mm (Sheet Extended)
Side	0.2in/5mm (Normal); 0.6in/15mm (Extended)
Memory	256 MB (upgradeable to 512 MB), 40 GB hard disk
Media	
Handling	Manual single-sheet feed, manual roll feed, automatic cutter
Types	Paper (plain, inkjet, coated, heavyweight coated, super heavyweight coated, semi-gloss, glossy, translucent bond, natural tracing, photo, vellum), film, canvas
Thickness (by paper path)	All paths: 0.0018 up to 0.0175 in/0.046 up to 0.450 mm
Weight (by paper path)	All paths: 0.11 up to 0.77 lb/50 up to 350 g/m2
Size	Sheets and rolls in sizes B, C, D, E and up to 42 in wide/A3, A2, A1, A0 and up to 1067 mm wide
Printing	
Technology	HP Thermal Inkjet
Technology resolution	HP Color Layering technology, PhotoREt III
Print cartridge colors	Black, cyan, magenta, yellow
Ink types	Black Pigmented, CMY dye-based
Ink drop	5.5 pl color, 15 pl black
Connectivity	
Interfaces Standard	Fast Ethernet (10/100 Mbps) (6, FireWire (IEEE-1394a compliant), 1 EIO slot
Interfaces Optional	HP Jetdirect 620n LAN card 🗸, HP Jetdirect 40d Gigabit Print Server for the HP Designjet 4000 Printer series 🤲 HP Designjet 4000 Printer series High speed USB 2.0 card
Drivers (included)	HP.GL/2, HP.RTL Windows drivers (NT 4.0 Workstation, NT 4.0 Server, ME, 98, 2000, XP, 2003), ADI driver for AutoCAD R14, support for AutoCAD 200x, Support for Citrix Metaframe
	environments.
	PS Windows drivers (© (NT 4.0 Workstation, NT 4.0 Server, ME, 98, 2000, XP, 2003), PS Mac drivers (© (OS 9.1, 9.2, 10.1, 10.2, 10.3)
Print languages (standard)	
HP Designjet 4000	HP.GL/2, HP.RTL, TIFF, JPEG, CALS-G4
HP Designjet 4000ps	Adobe® PostScript Level 3, Adobe® PDF 1.5, HPGL/2, HPRTL, TIFF, JPEG, CALS-G4
Dimensions (w x d x h)	
Maximum	76 x 31.5 x 53.2 in (1930 x 800 x 1350 mm)
Shipping	83.9 x 28 x 47.8 in (2130 x 710 x 1215 mm)
Weight	
Printer	253 lb (115 kg)
Shipping	387.8 lb (175.9 kg)
What's in the box	
HP Designjet 4000 Printer	HP Designjet 4000 Printer, Stand & Bin, Setup Poster, User's Documentation CD, software setup for Windows & Mac CD, Quick Reference Guide and Holder, Media sample, Maintenance Kit, Power Cord, 3-inch Spindle Adaptor, Printheads (8), Printhead Cleaners (8), Ink Cartridaes (4), Customer Service Guide
HP Designjet 4000ps Printer	HP Designiet 4000ps Printer, Stand & Bin, Setup Poster, User's Documentation CD, software setup for Windows & Mac CD, Quick Reference Guide and holder, Media sample, Maintenance Kit,
	Power Cord, 3-inch Spindle Adaptor, Printheads (8), Printhead Cleaners (8), Ink Cartridges (4), Customer Service Guide, Taiwan PostScript Fonts (for Taiwan localization only).
(1 Mechanical printing time Printed in East mode on HP Brid	ht White high Paper (Bond). Speed indicated is maximum printer speed. (6 TCP/P support only
(2 Printed in Fast mode on HP Bright White Inkjet Paper (Bon	d). Speed indicated is maximum printer speed. (7 TCP/IP, Appletalk, DLC/LLC and IPX/SPX protocols
(3 Multi-copy printing. Printed in Fast mode on HP Bright Wh	ite Inkjet Paper (Bond). Speed indicated is maximum printer speed.

Mechanical printing time. Printed in trad mote on nr triggin vinite implif roper (comp., percent inscared a musineme spece). Printel in fost mode on HP Brigh White linklye Pope (Bool). Speed indicated is maximum printer speed. Muli-copy printing. Printed in fost mode on HP Brigh White linklye Poper (Bool). Speed indicated is maximum printer speed. From 1200 x 1200 joint dpi ±0.1% of the specified vector length or ±0.1 mm (whichever greater) at 22°C (73°F), 50-60% relative hunkity, on AD printing material in Best or Normal mode with HP Matte film

Enviromental ranges

Operating temperature
Recommended operating temperature
Storage temperature
Operating humidity
Recomended humidity
Acoustic
Sound pressure, active
Sound pressure, standby
Sound power, active
Sound power, standby
Power consumption
Maximum
Standby

Power requirements

Power certification Safety certification

Electromagnetic compatibility

Energy Star compilant

Warranty

Accessories

Service and support Care packs

41 to 104° F/ 5 to 40° C 59 to 86° F/ 15 to 30° C -4 to 131° F/ 20 to 55° C 20 to 80% RH

25 to 75% RH 53 dB(A) 39 dB(A) 7.0 B(A) 5.7 B(A)

500 watts 105 watts

Input voltage 100 to 127/220 to 240 VAC (+/- 10%) auto range, 6/3 amp maximum, 50/60 Hz (+/- 3 Hz)

Compliant with IEC 60950, including EU IVD and EN60950, CSA certified for US and Canada, Mexico NYCE, Argentina IRAM, Singapore PSB, Russia VNIIS, Poland EL TEST Compliant with Class A requirements including EU (EMC Directive), USA (FCC rules), Canada (DoC), Australia (ACA), New Zealand (MaCO, Japan (VCCI), Karea (MIC), Taiwan (BSMI)

One-year next-business-day on-site

HP Designjet Roll Feed Spindle 42 inch (Q5675A), HP Jetdirect 40d Gigabit Print Server for the Designjet 4000 Printer series (Q5679A), HP Designjet 4000 Printer series High Speed USB 2.0 card (Q5680A), HP Designjet 4000 Printer series 256 MB Memory Upgrade (Q5673A), HP Jetdirect 620n LAN card (J7934A)

H7604A/E HP Installation Service (1 unit) H4518A/E HP Network Installation Service (1 unit) H5655A/E HP Next Business Day Onsite Hardware Support, 3 years H2816A/E HP 4 hour response 9x5 Onsite Hardware Support, 3 years H2816A/E HP 4 hour response 13x5 Onsite Hardware Support, 1 year post warranty H4038PA/PE HP Next Business Day Onsite Hardware Support, 1 year post warranty H4934PA/PE HP 4 hour response 9x5 Same-Day Onsite Hardware Support, 1 year post war-ranty

H5730PA/PE HP 4 hour response 13x5 Onsite Hardware Support, 1 year post warranty

Energy Star® Energy Star logo® are US registered marks of the United States Environmental Protection Agency. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. Adobe® and Adobe®PosiScript® 3™ are trademarks of Adobe Systems Incorporated. AutoCAD is a U.S. trademark of Autodesk, Inc. © 2004 Hewket:Rekard Development Company L.P.The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



For more information visit our website at www.hp.com/go/designjet4000

Orde	ring information
Product n	
	HP Designjet 4000 Printer
	HP Designjet 4000ps Printer
Accessori	
	HP Designjet Roll Feed Spindle 42 inch
	HP Designjet 4000 Printer series High Speed USB 2.0 card
	HP Designiet 4000 Printer series 256 MB Memory Upgrade
	and software
	HP Jetdirect 40d Gigabit Print Server for the Designjet 4000 Printer series
	HP Jetdirect 620n LAN card
Ink suppli	
	HP 90 Black Printhead and Cleaner
	HP 90 Cyan Printhead and Cleaner
	HP 90 Magenta Printhead and Cleaner
	HP 90 Yellow Printhead and Cleaner
	HP 90 Cyan Ink Cartridge, 225ml
	HP 90 Magenta Ink Cartridge, 225ml
	HP 90 Yellow Ink Cartridge, 225ml
	HP 90 Black Ink Cartridge, 400ml
	HP 90 Cyan Ink Cartridge, 400ml
	HP 90 Magenta Ink Cartridge, 400ml
	HP 90 Yellow Ink Cartridge, 400ml
	HP 90 Black Ink Cartridges, 400ml, 3-Ink Multipack
	HP 90 Cyan Ink Cartridges, 400ml, 3-Ink Multipack
	HP 90 Magenta Ink Cartridges, 400ml, 3-Ink Multipack
	HP 90 Yellow Ink Cartridges, 400ml, 3-Ink Multipack
	HP 90 Black Printhead/Cleaner & Ink Cartridge, 400ml, Value Pack
	HP 90 Cyan Printhead/Cleaner & Ink Cartridge, 400ml, Value Pack
	HP 90 Magenta PH/Cleaner & Ink Cartridge, 400ml, Value Pack
	HP 90 Yellow Printhead/Cleaner & Ink Cartridge, 400ml, Value Pack
Media	The yor follow Thinking all cleaner of hik cannage, foothis, faile fack
	HP Universal Inkjet Bond Paper (150 ft x 36 in)(45.7 m x 914 mm)
	HP Bright White Inkjet Bond Paper (150 ft x 36 in)(45.7 m x 914 mm)(NA and LAR only)
	HP Bright White Inkjet Bond Paper (150 ft x 36 in)(45.7 m x 914 mm)(AP and EMEA only)
	HP Coated Paper (150 ft x 36 in)(45.7 m x 914 mm)
	HP Heavyweight Coated Paper (100 ft x 36 in)(30.5 m x 914 mm)
	HP Natural Tracing Paper (150 ft x 36 in)(45.7 m x 914 mm)
	HP Translucent Bond (150 ft x 36 in)(45.7 m x 914 mm)
	HP Vellum (150 ft x 36 in)(45.7 m x 914 mm)
	HP Clear Film (75 ff x 36 in)(22.9 m x 914 mm)(NA, LAR, EMEA, AP only)
	HP Matte Film (125 ft x 36 in)(38.1 m x 914 min)(∞ , EAK, EMEA, Ar Only)
	HP Universal High-Gloss Photo Paper (100 ft x 36 in)(30.5 m x 914 mm)
	HP Productivity Photo Gloss (100 ft x 36 in)(30.5 m x 610 mm)(NA, EMEA, AP only)
	HP Productivity Photo Semi-Gloss (100 ff x 36 in)(30.5 m x 1067 mm)(NA, EMEA, AP only)
	HP Photo Paper RC Matte (100 ff x 36 in) (30.5 m x 914 mm)(NA, EMEA, AP (excluding JP)
	HP Proofing Paper RC Satin (75 ff x 36 in) (22.9 m x 914 mm) (NA, EMEA, AP (excluding JP)
	HP Universal Semi-gloss Photo Paper (100 ft x 36 in) (30.5 m x 914 m)

A complete list of supplies for the HP Designjet 4000 Printer series is available at www.hp.com/go/supplies

